

Titan Tool Interchangeability

** Recommended

T No.	Stockcode	Description	Max Load Cell**	Compatibility		Standards
				Titan5	Titan10	
T4	794-864	Button Holder (used with T27^ or T37)	1000			BS 4162, M&S P122 & Next TM37
T5	794-806	Pneumatic Yarn Grips (pair)^	200			ASTM D2256, ISO 2062
T8	794-686	Needle Clamp [Apparel Version] (used with T27)^	1000		with T27 only	ISO 13936-3
T9	794-687	Needle Clamp [Upholstery Version] (used with T27)^	1000		with T27 only	ISO 13936-3, IKEA IOS-PRG-0023
T12	794-934	Attachments Kit (can be used with T27^ or T37)	500			EN 71-1, M&S P115 & P124, Next TM42, TM45, TM46
(T12)	794-867	OctoGrip (use with T12)	200			
T13	794-844	Pile Loop Extraction Kit (used with T27^ or T37)	100			EN 15598
T14	794-933	Zip Testing Kit (used with T27^ or T37)	1000			BS 3084, ASTM D2061, EN 16732
T15	794-883	Pneumatic Yarn Grips (pair)^	1000			ASTM D2256, ISO 2062
T16	794-935	Attachments Kit (used with T12)	500			BS 7907, CEN/TR 16792
T18	794-889	Loop Bars (pair)^	200			BS 4952, EN 14704-1 Method B, ASTM D4964, Adidas 4.27
T19	794-891	Check Weight Set^	ALL			N/A
T20A	794-894	Clamp for Ball Burst and Puncture Tests*	5000			ASTM D751, D3787, D6797, GB/T 19976, WSP 110.5
T20A	794-895	Ball Probe*	5000			ASTM D751, D3787, D6797, GB/T 19976, WSP 110.5
T20B	794-839	Screwdriver Puncture Attachment*	5000			ASTM D751
T21	794-838	C-Clamps(pair)^ (formerly T11)	200			EN 14704-1 Method B, Adidas 4.27
T22	794-602	Hank Bollards / Skein Spools^	5000			ISO 6939, ASTM D1578
T23A	794-920	Manual Fabric Grips (5kN)^	5000			
T24	794-858	Button & Stud Holder (used with T27^ & T37)	1000			BS 7907, CEN/TR 16792
T25	794-931	Manual Yarn Grips (pair)^	1000			ASTM D2256, ISO 2062
T26	794-932	Bra Wire Penetration Tool (used with T27^ & T37)	1000			M&S P11A, Next TM36, Pacific Brands, PB-002, H&M DS-12
T27	794-927	Pneumatic Fabric Grips^	5000			
T28	794-936	Coefficient of Friction Fixture^	100			ASTM D1894, DIN 53375, ISO 9295, TAPPI T549
T29	794-937	Compression Platens (pair)	5000			LTD 18, IS 14625
T30	794-938	Tuft and Loop Withdrawal Kit^	200			ISO 4919
T32	794-835	EN 388 Nail Puncture Kit	1000			EN 388
T33	794-885	Baumann / Slit Tear Clamps^	200			ISO 3377-2, IUP 8, M&S P35
T34	794-882	ASTM Slit Tear Clamps^	200			ASTM D2212
T35	794-886	Adhesion of Finish Kit^	200			ISO 11644, IUF 470
T36	794-887	Leather Ball Burst^ (tension mode)	1000			ISO 3379, IUP 9, SLP 9, BS 3424, BS 3144 Method B
T37	794-940	Pneumatic Fabric Grips	10000			
T39	794-941*	T39 Circular compression Platens (pair), 155mm dia, stainless steel (10kN max)	10000			LTD 18, IS 14625

^Tooling adaptor required for use with Titan10

* Ball Probe & Screwdriver Puncture Attachment available upon request for Titan10